

Tolerant Junta Testing and the Connection to Submodular Optimization and Function Isomorphism

Eric Blais* Clément Canonne† Talya Eden‡ **Amit Levi***
Dana Ron‡

* University of Waterloo

† Stanford University

‡ Tel Aviv University

6.5.18

Juntas

Juntas

A function $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ is a **k -junta** if it depends on at most k of its variables.

Juntas

A function $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ is a **k -junta** if it depends on at most k of its variables.

Why should we care?

Juntas

A function $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ is a **k -junta** if it depends on at most k of its variables.

Why should we care?

- ▶ Juntas model learning in the presence of irrelevant attributes.

Juntas

A function $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ is a **k -junta** if it depends on at most k of its variables.

Why should we care?

- ▶ Juntas model learning in the presence of irrelevant attributes.
- ▶ Central object of study in the analysis of Boolean functions.

Juntas

A function $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ is a **k -junta** if it depends on at most k of its variables.

Why should we care?

- ▶ Juntas model learning in the presence of irrelevant attributes.
- ▶ Central object of study in the analysis of Boolean functions.
 - ▶ Approximates well other (complex) classes of functions.

Juntas

A function $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ is a **k -junta** if it depends on at most k of its variables.

Why should we care?

- ▶ Juntas model learning in the presence of irrelevant attributes.
- ▶ Central object of study in the analysis of Boolean functions.
 - ▶ Approximates well other (complex) classes of functions.
 - ▶ Connections to hardness of approximation.

(Tolerant) Testing Juntas

Given query access to unknown $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ and $0 < \varepsilon_1 < \varepsilon_2 < 1$:

(Tolerant) Testing Juntas

Given query access to unknown $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ and $0 < \epsilon_1 < \epsilon_2 < 1$:

- ▶ If f is ϵ_1 -close to a k -junta, accept w.p $2/3$.

(Tolerant) Testing Juntas

Given query access to unknown $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ and $0 < \epsilon_1 < \epsilon_2 < 1$:

- ▶ If f is ϵ_1 -close to a k -junta, accept w.p $2/3$.
- ▶ If f is ϵ_2 -far from any k -junta, reject w.p $2/3$.

(Tolerant) Testing Juntas

Given query access to unknown $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ and $0 < \epsilon_1 < \epsilon_2 < 1$:

- ▶ If f is ϵ_1 -close to a **k -junta**, accept w.p $2/3$.
- ▶ If f is ϵ_2 -far from any **k -junta**, reject w.p $2/3$.

Where

$$\text{dist}(f, g) = \Pr_{x \sim U}[f(x) \neq g(x)].$$

(Tolerant) Testing Juntas

Given query access to unknown $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ and $0 < \epsilon_1 < \epsilon_2 < 1$:

- ▶ If f is ϵ_1 -close to a k -junta, accept w.p $2/3$.
- ▶ If f is ϵ_2 -far from any k -junta, reject w.p $2/3$.

Where

$$\text{dist}(f, g) = \Pr_{x \sim U}[f(x) \neq g(x)].$$

Theorem ([FKRSS04, CG04, Bla09]).

For $\epsilon_1 = 0$, the query complexity for testing k -juntas is $\tilde{\Theta}(k/\epsilon_2)$.

(Tolerant) Testing Juntas

Given query access to unknown $f: \{-1, 1\}^n \rightarrow \{-1, 1\}$ and $0 < \epsilon_1 < \epsilon_2 < 1$:

- ▶ If f is ϵ_1 -close to a **k -junta**, accept w.p $2/3$.
- ▶ If f is ϵ_2 -far from any **k -junta**, reject w.p $2/3$.

Where

$$\text{dist}(f, g) = \Pr_{x \sim U}[f(x) \neq g(x)].$$

Theorem ([FKRSS04, CG04, Bla09]).

For $\epsilon_1 = 0$, the query complexity for testing k -juntas is $\tilde{\Theta}(k/\epsilon_2)$.

However, in many practical scenarios the function is not exactly a **k -junta** but **close** to such.

Our Results

Theorem 1.

There is an algorithm that for any $\varepsilon > 0$ satisfies the following:

Our Results

Theorem 1.

There is an algorithm that for any $\epsilon > 0$ satisfies the following:

- ▶ *If f is $\epsilon/10$ close to **k -junta**, then the algorithm accepts with high probability.*

Our Results

Theorem 1.

There is an algorithm that for any $\epsilon > 0$ satisfies the following:

- ▶ *If f is $\epsilon/10$ close to k -junta, then the algorithm accepts with high probability.*
- ▶ *If f is ϵ far from any $2k$ -junta, then the algorithm rejects with high probability.*

Our Results

Theorem 1.

There is an algorithm that for any $\epsilon > 0$ satisfies the following:

- ▶ If f is $\epsilon/10$ close to k -junta, then the algorithm accepts with high probability.
- ▶ If f is ϵ far from any $2k$ -junta, then the algorithm rejects with high probability.

The query complexity of the algorithm is $\text{poly}(k, 1/\epsilon)$.

Our Results

Theorem 1.

There is an algorithm that for any $\epsilon > 0$ satisfies the following:

- ▶ If f is $\epsilon/10$ close to k -junta, then the algorithm accepts with high probability.
- ▶ If f is ϵ far from any $2k$ -junta, then the algorithm rejects with high probability.

The query complexity of the algorithm is $\text{poly}(k, 1/\epsilon)$.

The proof uses a techniques from **submodular optimization**

Our Results

Theorem 2 (“Smooth Tradeoff”).

There is an algorithm that for any $\varepsilon > 0$ and $\rho \in (0, 1)$ satisfies the following:

Our Results

Theorem 2 (“Smooth Tradeoff”).

There is an algorithm that for any $\varepsilon > 0$ and $\rho \in (0, 1)$ satisfies the following:

- ▶ If f is $\rho\varepsilon/16$ close to k -junta, then the algorithm accepts with high probability.

Our Results

Theorem 2 (“Smooth Tradeoff”).

There is an algorithm that for any $\varepsilon > 0$ and $\rho \in (0, 1)$ satisfies the following:

- ▶ If f is $\rho\varepsilon/16$ close to k -junta, then the algorithm accepts with high probability.
- ▶ If f is ε far from any k -junta, then the algorithm rejects with high probability.

Our Results

Theorem 2 (“Smooth Tradeoff”).

There is an algorithm that for any $\varepsilon > 0$ and $\rho \in (0, 1)$ satisfies the following:

- ▶ If f is $\rho\varepsilon/16$ close to k -junta, then the algorithm accepts with high probability.
- ▶ If f is ε far from any k -junta, then the algorithm rejects with high probability.

The query complexity of the algorithm is $O\left(\frac{k \log k}{\varepsilon} \cdot \frac{1}{\rho(1-\rho)^k}\right)$.

Our Results

Theorem 3.

There is an algorithm that given query access to f and g and any $\epsilon > 0$ satisfies the following:

- ▶ If f and g are ϵ/c -close to **isomorphic**, then the algorithm accepts with high probability.
- ▶ If f and g are ϵ -far from **isomorphic**, then the algorithm rejects with high probability.

The query complexity of the algorithm is $O(2^{k^*/2}/\epsilon)$ where k^* is the smallest k such that either f or g are ϵ/c -close to a junta.

For more details, come talk to me during the poster session

Thanks